




VYBO Electric a.s.								
Data Sheet				No.				
Three Phase Induction Motor				Drawing No.				
Customer								
Client reference								
Type			4LC-355M 1-8 132KW 400/690V 50HZ					
Brand			VYBO Electric					
Identification								
Type:	4LC-355M 1-8		Frame:	355		mm		
Power:	132	kW	Poles:	8		P		
Rated Current:	380 V	255	A	Rated Voltage:	400	/	690 V	
	400 V	242		Connection:	Δ/Y			
	415 V	234		Insulation Class:	F			
Speed:	740	rpm	Temperature Rise:					
Frequency:	50	Hz	Service Factor:	1,0				
Direct on line starting torque ratio (LRT/RLT):	1,6		Duty:	S1, S2, S3, S4-S9				
Direct on line pull out torque ratio (BDT/RLT):	2		Ambient Temperature:	-35~50°C				
Direct on line starting current ratio (LRA/RLA):	7,7		Altitude:	1000m				
Efficiency:	94,9	%	Protection Degree:	IP55				
Power factor:	0,81		Cooling:	IC411				
Noise level:	89	dB(A)	Mounting:	IM B (On request)				
Weight:	2346	kg	Vibration:	2.8 mm/s				
Rotor inertia:	9,10554	kg/m2	Direction of Rotation:	Both				
			Starting Method:	DOL or VFD				
			Coupling:	DIRECT				
			Load Type:	Parabolic or linear curve				
			Terminal box:	2-M63X1.5				
			Bearing Information					
				DE		NDE		
			Bearing:	NU322C3		NU322C3		
			Regreasing int.(h):					
			Grease amount(g):					
Grease:								
Notes / Accessories			Deviation Sheet					
			VYBO Electric		Customer			
Standards								
Specification:	IEC60034-1 / GB755							
Test:	IEC60034-2 / GB/T1032							
Noise:	IEC60034-9 / GB10069.3							
Vibration:	IEC60034-14 / GB10068							
Edition								
Performed		Checked	Date					
Item	Changes		Performed	Checked	Date			